Devoted to the Commitments



Hydro Pneumatic Cylinders and Presses

Hydro Pneumatic Controls







H-Frame (2-Pillar)

Unique features include:-

- Heavy-Duty H-Frame for high force applications.
- Precision ground base plate with diagonal T-slots.
- Wider tool mounting area.
- High flexibility due to short retooling time.
- Virtually maintenance free operation resulting high up time.

H-Guides-4-Pillar

Unique features include:-

- Heavy-Duty Rigid 4-Pillar for high force applications.
- Precision ground base plate with diagonal T-slots.
- Larger tool mounting area.
- High flexibility due to short retooling time.
- Minimum maintenance = High production





C-Frame

Unique features include:-

- Heavy-Duty Rigid fabricated frame for high force applications.
- Precision ground base plate with diagonal T-slots. Larger tool mounting area.
- High flexibility due to short retooling time.
- Minimum maintenance = High production

2pillar / 4pillar / C frame	Ranges
Tonnages	2tonne / 4 Tonne / 8 Tonne / 15 tonne / 30 Tonne
Approach Stroke	50 mm / 75 mm / 100mm / 150 mm
Power Stroke	6 mm / 12mm / 24 mm
Air Pressure Required	Maximum 6 Bar Min 3 Bar
Air Quality	Filtered (40 Microns) Lubricated.
Electrical Power	230 V AC/ 5 Amps
Compressor Capacity	Contact our technical team.